

# Current Probes

## A621 & A622 Datasheet



The A600 Series current probes are specifically designed to support measurements with the TekMeter® or oscilloscope.

### Features and benefits

- A621
  - AC – 5 Hz to 50 kHz
  - 100 mA to 2000 A peak
  - For DMMs and oscilloscopes
  - Clamp on

- A622
  - AC/DC – 100 kHz
  - 50 mA to 100 A peak
  - For DMMs and oscilloscopes

### Applications

- Motor drives
- Inverters
- Power supplies
- Avionics

### A621 2000 Amp AC Current probe/BNC

This industrial-style clamp-on probe has a BNC connector and can be used with a shrouded banana plug adapter <sup>1</sup> so it can be used on digital multimeters, TekMeter, and oscilloscopes. The A621 can measure AC currents from 100 mA to 2000 A peak over a frequency range of 5 Hz to 50 kHz. It provides a 1 mV, 10 mV, or 100 mV output for each Amp measured.

### A622 100 Amp AC DC Current probe/BNC

This "long nose" style clamp-on probe uses a Hall Effect current sensor to provide a voltage output to oscilloscopes. It has a BNC connector and can be used with a shrouded banana plug adapter <sup>1</sup> so it can also be used on digital multimeters, TekMeter, and oscilloscopes. The A622 can measure AC/DC currents from 50 mA to 100 A peak over a frequency range of DC to 100 kHz. It provides 10 mV or 100 mV output for each Amp measured.

### Recommended products

TPS2000, TDS1000B, TDS2000C, and TDS3000C Series oscilloscopes and DMM4020 <sup>1</sup>, DMM4040 <sup>1</sup>, and DMM4050 <sup>1</sup> digital multimeters.

<sup>1</sup> For instruments with banana jack inputs, Tektronix part number 012-1450-00 Female BNC to banana lead adapter is required.

## Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

Characteristic	A621	A622
Frequency range	5 Hz to 50 kHz	DC to 100 kHz
Maximum input current	2000 A peak	100 A peak
Output	1 mV/A, 10 mV/A, 100 mV/A	10 mV/A, 100 mV/A
Maximum conductor diameter	54 mm (2.13 in.)	11.8 mm (0.46 in.)
Termination	BNC <sup>1</sup>	BNC <sup>1</sup>
Maximum bare-wire voltage	600 V (CAT III)	600 V (CAT III)
Safety	UL3111-2-032, CSA1010.2.032, EN61010-2-032, IEC61010-2-032	UL3111-2-032, CSA1010.2.032, EN61010-2-032, IEC61010-2-032

## Ordering information

A621	2000 A AC Current probe/BNC.
A622	100 A AC/DC Current probe/BNC.

## Recommended accessories

012-1450-xx	Adapter, lead; discrete – MLD, 2, 18 AWG, dual insul, BNC, female X 4 mm dual insul; banana jack X dual insul plug, shield banana
-------------	---

## Options

### Service options

Opt. R3	Repair Service 3 Years (including warranty)
Opt. R5	Repair Service 5 Years (including warranty)



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



