



# 9603D Dual-Tracking Regulate DC Power Supply



## PRODUCT FEATURES

- Triple Output
- Auto Series and Parallel Operation
- Constant Voltage and Constant Current Operation
- Overload and Reverse Polarity Protection
- Heatsink with a Fan and have the Auto 2-step Control to Reduce the Noise
- 5V, 3A Fixed Output
- Auto Tracking
- Low Ripple Noise
- 0.01% High Regulation
- Full 3 Digits 0.52" Red LED Display
- CE marking
- Meet IEC 61010-1:2001

## SPECIFICATIONS

MODEL NAME	9603D	
OUTPUT VOLTAGE	0~60V×2	5V
OUTPUT CURRENT	0~3A×2	3A
OPERATION MODE	Two Independent Output and 5V Fixed Output	
Independent	Output from 0 to Rating Voltages and Rating Currents	
Series	Output from 0 to +/- Rating Voltages at Rating Current Each	
Parallel	Output from 0 to Double Rating Voltages at Rating Currents Output from 0 to Double Currents at Rating Voltages	
CONSTANT VOLTAGE	$\leq 0.01\% + 5mV$ $\leq 0.01\% + 3mV$ $\leq 50\mu s$ (50% to 100% Load Change) $\leq 1mV_{rms}$ $\leq 300ppm/^{\circ}C$	
CONSTANT CURRENT	$\leq 0.06\% + 4mA$ $\leq 0.06\% + 4mA$ $\leq 3mA_{rms}$	
DISPLAY ACCURACY	$\pm 0.5\% + 2digits$	
Display Mode	3 1/2 Digits Red LED Display×4	
TRACKING OPERATION	$\leq 0.2\% + 50mV$ $\leq 300mV$	
5V FIXED OUTPUT	Load Regulation $\leq 10mV$ Line Regulation $\leq 5mV$ $\leq 2mV_{rms}$ Voltage Accuracy $5V \pm 0.25V$ Output Current 3A	
POWER SOURCE	ACV 100/120/220/240±10% , 60/50Hz	
OPERATION TEMP. & HUMIDITY	5°C to 40°C, <80%	
STORAGE TEMP. & HUMIDITY	-10°C to 70°C, <80%	
DIMENSIONS	270(W) x 156(H) x 462(D)mm	
WEIGHTS	18.5Kg	
SAFETY & EMC	CE (include EMC & LVD)	

**LOCK 洛克儀器股份有限公司**

[台北] 新北市中和區中正路764號6樓 (02)3234-6000

[新竹] 新竹市北區光華二街72巷79號 (03)532-4199

www.lockinc.com.tw www.pcstore.com.tw/lock